

# LOW-VOLTAGE PLUGS AND SOCKET OUTLETS

according to IEC 60309, EN 60309, VDE 0623


**turn2fix**



## CONNECTOR

splash-proof IP44

- screw terminals
- quick release locking system (turn2fix)
- nickel-plated contacts



POLES	2	3	2	3
AMPERE	16		32	

a	150	150	150	150
b	75	75	75	75
c	48	48	48	48
K	9,5-24	9,5-24	9,5-24	9,5-24
Weight [g/each]	179	199	179	199

VOLTAGE	24 V~	42 V~	24/42 V~
FREQUENCY	50/60 HZ	50/60 HZ	100-200 HZ
DESIGNATION	WITHOUT AUXILIARY NOTCH	12H	4H

AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
16	2	K01S20	K01S60	K01S10	10
16	3	K11S20	K11S60	K11S10	10
32	2	K02S20	K02S60	K02S10	10
32	3	K12S20	K12S60	K12S10	10


**turn2fix**



## CONNECTOR

watertight IP67

- screw terminals
- quick release locking system (turn2fix)
- nickel-plated contacts



POLES	2	3	2	3
AMPERE	16		32	

a	150	150	150	150
b	78	78	78	78
c	48	48	48	48
K	9,5-24	9,5-24	9,5-24	9,5-24
Weight [g/each]	199	219	199	219

VOLTAGE	24 V~	42 V~	24/42 V~
FREQUENCY	50/60 HZ	50/60 HZ	100-200 HZ
DESIGNATION	WITHOUT AUXILIARY NOTCH	12H	4H

AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
16	2	K01S25	K01S65	K01S15	10
16	3	K11S25	K11S65	K11S15	10
32	2	K02S25	K02S65	K02S15	10
32	3	K12S25	K12S65	K12S15	10