


# RCCB – SENSITIVE TO ALTERNATING CURRENT TYPE AC

Undelayed tripping acc. to IEC 61008



RATED RESID. CURRENT $I_{\Delta n}$ mA	RATED CURRENT $I_n$ A	SURGE CURRENT STRENGTH > A	MAX. BACK-UP FUSE A	MODULES	ITEM NO.	WEIGHT g/EACH	PACK-ING UNIT
--	-----------------------------	-------------------------------	------------------------	---------	----------	------------------	---------------

4-pole, undelayed tripping							
30	16	250	63	4	<b>RW4103</b>	450	1
100	16	250	63	4	<b>RW4110</b>	450	1
300	16	250	63	4	<b>RW4130</b>	450	1
30	25	250	63	4	<b>RW4203</b>	450	1
100	25	250	63	4	<b>RW4210</b>	450	1
300	25	250	63	4	<b>RW4230</b>	450	1
30	40	250	63	4	<b>RW4303</b>	450	1
100	40	250	63	4	<b>RW4310</b>	450	1
300	40	250	63	4	<b>RW4330</b>	450	1
30	63	250	100	4	<b>RW4403</b>	450	1
100	63	250	100	4	<b>RW4410</b>	450	1
300	63	250	100	4	<b>RW4430</b>	450	1
30	80	250	125	4	<b>RW4503</b>	470	1
300	80	250	125	4	<b>RW4530</b>	470	1
500	80	250	125	4	<b>RW4550</b>	470	1
30	100	250	125	4	<b>RW4603</b>	470	1
100	100	250	125	4	<b>RW4610</b>	470	1
300	100	250	125	4	<b>RW4630</b>	470	1
30	125	250	125	4	<b>RW4703</b>	470	1
100	125	250	125	4	<b>RW4710</b>	470	1
300	125	250	125	4	<b>RW4730</b>	470	1
500	125	250	125	4	<b>RW4750</b>	470	1