

PLUGS


ACCORDING TO IEC 60309, EN 60309, VDE 0623



PLUG

watertight IP67

- screw terminals
- quick release locking system (turn2fix)
- nickel-plated contacts



POLES	3	4	5	3	4	5
AMPERE	16			32		

a	122	128	134	150	150	155
b	71	79	87	93	93	100
K	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
SW	42	42	42	50	50	50
Weight [g/each]	130	154	183	223	242	276

VOLTAGE	110 V~	230 V~	230 V~	400 V~	440 V~	500 V~
FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
DESIGNATION	4h	3p = 6h 4p/5p = 9h	1h	3p = 9h 4p/5p = 6h	11h	7h


AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
16	3	S31S15	S31S25	S31S05			S31S55	10
16	4	S41S15	S41S25		S41S35	S41S45	S41S55	10
16	5		S51S25	S51S05	S51S35		S51S55	10
32	3	S32S15	S32S25	S32S05			S32S55	10
32	4	S42S15	S42S25		S42S35	S42S45	S42S55	10
32	5		S52S25	S52S05	S52S35		S52S55	10



PLUG

splash-proof IP44

- HighPower version
- nickel-plated contacts
- with pilot contact
- screw terminals



POLES	3	4	5
AMPERE	63		

a	257	257	257
b	190	190	190
c	102	102	102
K	14,5-36	14,5-36	14,5-36
Weight [g/each]	530	572	621

VOLTAGE	230 V~	400 V~	500 V~
FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz
DESIGNATION	3p = 6h 4p/5p = 9h	3p = 9h 4p/5p = 6h	7h

AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
63	3	S33S20		S33S50	2
63	4	S43S20	S43S30	S43S50	2
63	5	S53S20	S53S30	S53S50	2