

MINIATURE CIRCUIT BREAKERS DC PRODUCT RANGE

6 kA B and C characteristic acc. to IEC 60898-2



6000 T15 **twin** *fix*

RATED CURRENT I_n A	CHARACTERISTIC		WEIGHT g / EACH	PACKING UNIT
	B ITEM NO.	C ITEM NO.		

1-pole				
0.5		C0.5DC1	120	12
1	B1DC1	C1DC1	120	12
2	B2DC1	C2DC1	120	12
3	B3DC1	C3DC1	120	12
4	B4DC1	C4DC1	120	12
6	B6DC1	C6DC1	120	12
10	B10DC1	C10DC1	120	12
13	B13DC1	C13DC1	120	12
16	B16DC1	C16DC1	120	12
20	B20DC1	C20DC1	120	12
25	B25DC1	C25DC1	120	12
32	B32DC1	C32DC1	120	12
40	B40DC1	C40DC1	120	12
50	B50DC1	C50DC1	120	12
63	B63DC1	C63DC1	120	12



6000 T15 **twin** *fix*

2-pole				
0.5		C0.5DC2	240	6
1	B1DC2	C1DC2	240	6
2	B2DC2	C2DC2	240	6
3	B3DC2	C3DC2	240	6
4	B4DC2	C4DC2	240	6
6	B6DC2	C6DC2	240	6
10	B10DC2	C10DC2	240	6
13	B13DC2	C13DC2	240	6
16	B16DC2	C16DC2	240	6
20	B20DC2	C20DC2	240	6
25	B25DC2	C25DC2	240	6
32	B32DC2	C32DC2	240	6
40	B40DC2	C40DC2	240	6
50	B50DC2	C50DC2	240	6
63	B63DC2	C63DC2	240	6