


ACCESSORIES FOR MOTOR PROTECTIVE CIRCUIT BREAKERS MS





FILE E 137938



	RATED OPERATING VOLTAGE	ITEM NO.	WEIGHT g/EACH	PACKING UNIT
--	-------------------------	----------	---------------	--------------

Shunt trip for inside mounting with connecting cable (140 mm long)				
	110 V 50 Hz, 120 V 60 Hz	AMS110	75	10
	220-230V 50 Hz, 240 V 60 Hz	AMS220	75	10
	380-415 V 50 Hz, 440 V 60 Hz	AMS380	75	10
	24 V 50/60 Hz	AMS24	75	10
	500 V 50 Hz	AMS500	75	10
	24 V DC	AMSD24	75	10
Pull-in voltage $0,7 \times U_e$			Switch in duration for U_e 100% AC	



Undervoltage trip for inside mounting with connecting cable (140 mm long)				
	110 V 50 Hz, 120 V 60 Hz	UMS110	75	10
	220-230 V 50 Hz, 240 V 60 Hz	UMS220	75	10
	380-415 V 50 Hz, 440 V 60 Hz	UMS380	75	10
	24 V 50/60 Hz	UMS24	75	10
	500 V 50 Hz	UMS500	75	10
Pull-in voltage $\geq 0.85 \times U_e$		Drop out voltage $0,35 - 0,7 \times U_e$		Switch in duration for U_e
				100%