

WALL-MOUNTED INLETS

ACCORDING TO IEC 60309, EN 60309, VDE 0623




WALL-MOUNTED INLET

watertight IP67

- HighPower version
- nickel-plated contacts with pilot contact
- screw terminals
- cable entry above, below or behind
- housing can be rotated 180°
- including blank screw connection

Watertight cap see page 21



b = Height, Angle = 15°

POLES	3	4	5
AMPERE	63		

a	271	271	271
b	175	175	175
Weight [g/each]	812	864	914

VOLTAGE	230 V~	400 V~	500 V~
FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz
DESIGNATION	3p = 6h 4p/5p = 9h	3p = 9h 4p/5p = 6h	7h

AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
63	3	G33S25		G33S55	2
63	4	G43S25	G43S35	G43S55	2
63	5	G53S25	G53S35	G53S55	2




WALL-MOUNTED INLET

watertight IP67

- HighPower version
- nickel-plated contacts with pilot contact
- screw terminals
- cable entry above, below or behind
- housing can be rotated 180°
- including blank screw connection

Watertight cap see page 21



b = Height, Angle = 15°

POLES	3	4	5
AMPERE	125		

a	387	387	387
b	209	209	209
Weight [g/each]	1620	1725	1834

VOLTAGE	230 V~	400 V~	500 V~
FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz
DESIGNATION	3p = 6h 4p/5p = 9h	3p = 9h 4p/5p = 6h	7h

AMPERE	POLES	ITEM NO.	ITEM NO.	ITEM NO.	PACKING UNIT
125	3	G34S25		G34S55	1
125	4	G44S25	G44S35	G44S55	1
125	5	G54S25	G54S35	G54S55	1