

MINIATURE CIRCUIT BREAKERS T PRODUCT RANGE

10 kA B, C and D characteristic acc. to IEC 60898-1

10 kA K and Z characteristic acc. to IEC 60947-2



RATED CURRENT I_n A	CHARACTERISTIC					WEIGHT g / EACH	PACKING UNIT
	B ITEM NO.	C ITEM NO.	D ITEM NO.	K ITEM NO.	Z ITEM NO.		

3-pole with switched neutral							
0.3		C0.3T9	D0.3T9	K0.3T9		480	3
0.5		C0.5T9	D0.5T9	K0.5T9		480	3
0.8		C0.8T9	D0.8T9	K0.8T9		480	3
1	B1T9	C1T9	D1T9	K1T9		480	3
1.6		C1.6T9	D1.6T9	K1.6T9		480	3
2	B2T9	C2T9	D2T9	K2T9		480	3
2.5		C2.5T9	D2.5T9	K2.5T9		480	3
3	B3T9	C3T9	D3T9	K3T9		480	3
3.5		C3.5T9	D3.5T9	K3.5T9		480	3
4	B4T9	C4T9	D4T9	K4T9		480	3
5	B5T9	C5T9	D5T9	K5T9		480	3
6	B6T9	C6T9	D6T9	K6T9		480	3
8		C8T9	D8T9	K8T9		480	3
10	B10T9	C10T9	D10T9	K10T9		480	3
13	B13T9	C13T9	D13T9	K13T9		480	3
16	B16T9	C16T9	D16T9	K16T9		480	3
20	B20T9	C20T9	D20T9	K20T9		480	3
25	B25T9	C25T9	D25T9	K25T9		480	3
32	B32T9	C32T9	D32T9	K32T9		480	3
40	B40T9	C40T9	D40T9	K40T9		500	3
50	B50T9	C50T9	D50T9 *	K50T9		540	3
63	B63T9	C63T9	D63T9 *	K63T9		540	3



4-pole							
0.3		C0.3T4	D0.3T4	K0.3T4		480	3
0.5		C0.5T4	D0.5T4	K0.5T4		480	3
0.8		C0.8T4	D0.8T4	K0.8T4		480	3
1	B1T4	C1T4	D1T4	K1T4		480	3
1.6		C1.6T4	D1.6T4	K1.6T4		480	3
2	B2T4	C2T4	D2T4	K2T4		480	3
2.5		C2.5T4	D2.5T4	K2.5T4		480	3
3	B3T4	C3T4	D3T4	K3T4		480	3
3.5		C3.5T4	D3.5T4	K3.5T4		480	3
4	B4T4	C4T4	D4T4	K4T4		480	3
5	B5T4	C5T4	D5T4	K5T4		480	3
6	B6T4	C6T4	D6T4	K6T4		480	3
8		C8T4	D8T4	K8T4		480	3
10	B10T4	C10T4	D10T4	K10T4		480	3
13	B13T4	C13T4	D13T4	K13T4		480	3
16	B16T4	C16T4	D16T4	K16T4		480	3
20	B20T4	C20T4	D20T4	K20T4		480	3
25	B25T4	C25T4	D25T4	K25T4		480	3
32	B32T4	C32T4	D32T4	K32T4		480	3
40	B40T4	C40T4	D40T4	K40T4		500	3
50	B50T4	C50T4	D50T4 *	K50T4		540	3
63	B63T4	C63T4	D63T4 *	K63T4		540	3

* only in 6 kA available