

OUTLET BOXES

with screw terminals
compliant with VDE 0606



THERMOPLASTIC OUTLET BOX

for surface mounting
cover with snap lock
terminals: 5 x 2,5 to* 6 mm²

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
white	2505010	80	10



THERMOPLASTIC OUTLET BOX

for flush mounting and surface mounting · cover with snap lock · terminals: 5 x 2,5 to* 6 mm²

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
white	2505110	80	10



THERMOPLASTIC OUTLET BOX

for flush mounting and surface mounting, claw bracket can be snapped out
cover with snap lock
terminals: 5 x 2,5 to* 6 mm²

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
white	2505210	90	10



BASE PLATE IP44

with two cable entries
for outlet boxes 25055

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
white	2505018	32	10



THERMOPLASTIC OUTLET BOX

for flush mounting
flat version · cover with snap lock
terminals: 5 x 2,5 mm²
extra flat – only 11 mm

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
white	2506110	61	10



THREE-CHAMBER OUTLET BOX

for flush mounting and surface mounting
dowel fastening
terminals: 5 x 2,5 to* 6 mm² / 7 x 2,5 mm²

COLOUR	ITEM NO.	WEIGHT g/EACH	PU
white	2518610	166	5

* if conductor section is > 5 x 2,5 mm²
use additional strain relief.