

ACCESSORIES MINIATURE CIRCUIT BREAKERS


S, SL,T and DC product ranges



Shunt trip

MODULE	RATED OPERATING VOLTAGE	MAX. OPERATING CURRENT AT U_n (T < 10 ms)	ITEM NO.	WEIGHT g / EACH	PACKING UNIT
1	12 V UC	1,3 A	FL12	105	5
1	24 V UC	0,6 A	FL24	105	5
1	48 - 72 V UC	0,2 A	FL48	105	5
1	110-230 V UC, 400 V AC	0,25 A bei 110 V	FL110	105	5
		0,5 A bei 230 V			
		0,8 A bei 400 V			

Pull-in voltage $0.7 \times U_e$ Switch in duration at U_e 100%



**Single Pole Miniature Circuit Breaker, 10 A,
B Characteristic for the special designation of circuits e.g. fire warning and telephone systems etc.**

RATED CURRENT I_n [A]	ITEM NO.	WEIGHT g / EACH	PACKING UNIT
10	B10T1R	150	12



Distance device 9 mm

MODULE	ITEM NO.	WEIGHT g / EACH	PACKING UNIT
$1/2$	ISD	13	10



Lock-off/Lock-on device

ITEM NO.	WEIGHT g / EACH	PACKING UNIT
EASS	2	10