


MINIATURE CIRCUIT BREAKERS S PRODUCT RANGE

6 kA B and C characteristic acc. to IEC 60898-1



| RATED CURRENT I_n A | CHARACTERISTIC | | WEIGHT g / EACH | PACKING UNIT |
|--------------------------|----------------|---------------|--------------------|-----------------|
| | B ITEM NO. | C ITEM NO. | | |

| 1-pole | | | | |
|--------|--------------|--------------|-----|----|
| 6 | B6S1 | C6S1 | 120 | 12 |
| 10 | B10S1 | C10S1 | 120 | 12 |
| 13 | B13S1 | C13S1 | 120 | 12 |
| 16 | B16S1 | C16S1 | 120 | 12 |
| 20 | B20S1 | C20S1 | 120 | 12 |
| 25 | B25S1 | C25S1 | 120 | 12 |
| 32 | B32S1 | C32S1 | 120 | 12 |



| 3-pole | | | | |
|--------|--------------|--------------|-----|---|
| 6 | B6S3 | C6S3 | 360 | 4 |
| 10 | B10S3 | C10S3 | 360 | 4 |
| 13 | B13S3 | C13S3 | 360 | 4 |
| 16 | B16S3 | C16S3 | 360 | 4 |
| 20 | B20S3 | C20S3 | 360 | 4 |
| 25 | B25S3 | C25S3 | 360 | 4 |
| 32 | B32S3 | C32S3 | 360 | 4 |

