



MOTOR PROTECTIVE CIRCUIT BREAKERS MA

IEC 60947



RATED CURRENT [A]	MAX. RATED OPERATING POWER (KW/AC 3)			OPERATING CURRENT SHORT CIRCUIT TRIP [A]	ITEM NO.	WEIGHT G / EACH	PACKING UNIT
	400/415 V	500 V	690 V				

MA with overload and short circuit tripping
 Temperature compensation from +20°C bis +40°C adjustable 

0,1 – 0,16	–	–		1,92	MA016M	450	1
0,16 – 0,25	0,06	0,06		3	MA025M	450	1
0,25 – 0,4	0,09	0,12		4,8	MA040M	450	1
0,4 – 0,63	0,12	0,25		7,6	MA063M	450	1
0,63 – 1	0,25	0,37		12	MA1.0M	450	1
1 – 1,6	0,55	0,75		19,2	MA1.6M	450	1
1,6 – 2,5	0,75	1,1		30	MA2.5M	450	1
2,5 – 4	1,5	2,2		48	MA4.0M	450	1
4 – 6,3	2,2	3		75,6	MA6.3M	450	1
6,3 – 10	4	4		120	MA10M	450	1
10 – 16	7,5	9		192	MA16M	450	1
16 – 20	9	12,5		240	MA20M	450	1
20 – 25	12,5	15		300	MA25M	450	1
25 – 32	15	18,5		348	MA32M	450	1
32 – 40	18,5	22		480	MA40M	450	1